

6. The method of claim 5, further comprising:
constructing, prior to receiving the message, a database mapping one or more
members of the user group with respective pager IDs and subscriber units;
upon identifying the target pager ID, consulting the database to determine
whether the target pager ID corresponds to a member of the user group; and
if the target pager ID corresponds to a member of the user group, identifying
the member as the target recipient, thereby determining that the target recipient is
a member of the user group.

7. The method of claim 6, wherein the step of identifying a subscriber unit
associated with the target recipient comprises, upon determining that the target
pager ID corresponds to a member of the user group, consulting the database to
identify the subscriber unit corresponding to the target pager ID.

8. In a radio communication system including a plurality of users defining a
user group, a method comprising:
receiving a paging message communicated via a paging service
communication protocol;

determining a target recipient of the paging message;

if the target recipient is a member of the user group,
identifying a communication unit associated with the target recipient, the
communication unit being operable to receive messages communicated via a
wireless protocol other than the paging service communication protocol; and
if the communication unit is logged on the radio communication system,
converting the paging message to the wireless protocol, yielding a converted
message, and sending the converted message to the communication unit.

9. The method of claim 8, performed by one or more infrastructure devices of
the radio communication system.

10. The method of claim 8, wherein the paging service protocol comprises one of: FLEX-TD, FLEX and POCSAG.

11. The method of claim 8, further comprising:

5 constructing, prior to receiving the paging message, a database mapping one or more members of the user group with respective pager IDs and communication units;

upon identifying the target pager ID, consulting the database to determine whether the target pager ID corresponds to a member of the user group; and

10 if the target pager ID corresponds to a member of the user group, identifying the member as the target recipient, thereby determining that the target recipient is a member of the user group.

12. The method of claim 11, wherein the step of identifying a communication unit associated with the target recipient comprises consulting the database to identify the communication unit of the target recipient.

13. A radio communication system comprising:

a receiver operable to receive paging messages communicated via a paging service communication protocol;

a decoder operable to decode the paging messages to identify respective target recipients of the paging messages;

a paging server for determining whether the target recipients are members of a user group and, if a target recipient is a member of the user group, identifying a communication unit associated with the target recipient;

a controller for converting the paging message to a wireless protocol of the communication unit, yielding a converted message; and

a transmitter for sending the converted message to the communication unit associated with the target recipient.

30